

# XCHEM

## TECHNICAL DATA SHEET

### FORTSEAL EXHAUST SEALER

#### DESCRIPTION

Fortseal Exhaust Sealer is a sodium silicate based sealer which sets at high temperatures.

#### KEY PROPERTIES

- Fortseal Exhaust Sealer is easy to apply and sets quickly under high temperatures.
- Fortseal Exhaust Sealer has excellent adhesion to metal.
- Fortseal Exhaust Sealer is conveniently packaged for both small and big applications.

#### KEY APPLICATIONS

Fort-tite Exhaust Sealer is used for sealing holes and cracks in exhaust pipes.

#### DIRECTIONS FOR USE

- Clean damaged or leaking area with a wire brush or scraper.
- Run the motor for a short period to warm the exhaust.
- When the exhaust is warm enough apply the sealer by hand exerting enough pressure to ensure a good key.
- Reinforce large cracks or holes with wire mesh.
- Run the motor again for about 15 minutes at a slow speed, to accelerate hardening.
- Use warm water to soften the sealer.

#### STORAGE AND STABILITY

- Resecure the component container tightly with the lid.
- Wash hands and tools immediately after use with soap and hot water.
- Fortseal exhaust sealer has a 6 month shelf life if kept under dry and cool conditions.

#### SAFETY PRECAUTIONS

- Protective clothing/gloves should be worn when handling Fortseal Exhaust Sealer.
- Ensure good ventilation or alternatively wear a protective mask.
- In case of skin contact immediately wash away using soap and warm water.
- In case of eye contact immediately rinse the affected eye(s) using plenty of clean water. **Immediately** contact a doctor.
- Keep away from children and in case of any ingestion, contact a doctor or health worker immediately.

The data and recommendations concerning this product are the result of extensive XCHEM laboratory testing and experience. As the use of the product is beyond our control, no warranty is expressed or implied and the customer should satisfy him/her self as to the suitability for this particular application.



Tel (012) 661 77 11  
Fax (012) 661 77 22